



Chad Lipscomb, PE, CPESC  
Director, Technical Services  
Western Excelsior Corporation  
PO Box 270308  
Fort Collins, CO 80527-0308  
970-631-8366 office  
chad@westernexcelsior.com

"Blanketing Nature With Nature"

---

Effective: 2/10/10

RE: Certificate of Conformance: *Excel R-1 Rapid Go*<sup>TM</sup>

To Whom it May Concern:

This letter is to certify that Western Excelsior manufactures the Rolled Erosion Control Product (RECP) marketed as EXCEL R-1 Rapid Go. Each blanket is subjected to Western Excelsior's Quality Assurance Program and is manufactured to the specifications listed in document number WE\_EXCEL\_R1RG\_SPEC. Further, Western Excelsior utilizes industry standardized test procedures to develop performance references for Excel R-1. Document number WE\_EXCEL\_R1RG\_PERF presents the industry standardized testing and results. Installation instructions are provided in document numbers WE\_EXCEL\_R1RG\_SII and WE\_EXCEL\_R1RG\_CII for hill slope and channel installations, respectively. A copy of document number WE\_EXCEL\_R1RG\_SPEC is attached; all other documentation may be obtained by calling Western Excelsior Technical Services at 1-800-967-4009, at [www.westernexcelsior.com](http://www.westernexcelsior.com) or by email at [wexcotech@westernexcelsior.com](mailto:wexcotech@westernexcelsior.com).

Regards,

A handwritten signature in black ink, appearing to read "Chad M. Lipscomb".

Chad M. Lipscomb, PE, CPESC  
Director, Technical Services  
Western Excelsior Corporation



## Material Properties and Dimensions



### Description

Western Excelsior manufactures a full line of Rolled Erosion Control Products (RECPs). Excel R-1 Rapid Go temporary Erosion Control Blanket is composed of a 100% machine produced High Altitude Rocky Mountain Aspen Excelsior matrix mechanically (stitch) bonded on two inch centers to a single photodegradable, synthetic net. The excelsior matrix consists of curled, machine produced fibers with greater than eighty percent longer than six inches. Excel R-1 Rapid Go blanket is available in natural color or dyed green and is recommended for use in channels or slopes requiring erosion protection for a period up to fifteen months. Actual field longevity is dependent on soil and climatic conditions.

### Specifications

Each roll of Excel R-1 Rapid Go is manufactured under Western Excelsior’s Quality Assurance Program to ensure a continuous distribution of fibers and consistent thickness. Verified values are provided in Table 1 and product characteristics are provided in Tables 2 and 3. Values provided in Tables 1, 2 and 3 represent expected values at the time of manufacture. Installation instructions and performance data are available from Western Excelsior’s Technical Support Division.

Tested Property	Test Method	Value	Units
Tensile Strength	ASTM D6818	5.0 (MD), 4.0 (TD)	lb/in
Elongation	ASTM D6818	12 (MD), 10 (TD)	%
Mass per Unit Area	ASTM D6475	9.1	oz/yd <sup>2</sup>
Thickness	ASTM D6525	8.4	mm
Light Penetration	ASTM D6567	37	% open
Water Absorption	ASTM D1117	275	%

Top Net	Synthetic Photo-degradable
Bottom Net	N/A
Top Net Opening	1.00 in x 0.75 in (Nominal)
Bottom Net Opening	N/A

Style	Narrow	Wide
Roll Width	4 ft	8 ft
Roll Length	180 ft	90 ft
Coverage	80 yd <sup>2</sup>	80 yd <sup>2</sup>
Roll Weight	51 lbs	51 lbs

Document # WE\_EXCEL\_R1RG\_SPEC. This document has been developed to provide the characteristic properties of the product described. For questions, to request performance data or installation recommendations, contact Western Excelsior at 800-967-4009 or wexcotech@westernexcelsior.com. Updated 02/10.